


MBB R 1500 SK MBB R 2000 LK



- Specially designed for motor vehicles with low-mount coupling systems
- 1,500/2,000 kg lifting capacity with four cylinders and 750/1,000 mm load distance
- Simple-fold platform
- Great freedom of motion for drawbar thanks to space-saving main beam
- Optimal adaptation to motor vehicles thanks to a wide range of different lifting arm lengths and pitches
- All-aluminium or steel/aluminium platform design
- Spring-supported folding part
- Platform package serves as underride guard
- Bridging projection for espagnolettes
- Powerful moving cylinder for horizontal positioning of the tail lift
- Moving rails in steel as standard, optionally available in aluminium
- Optionally available completely pre-assembled with energy chain

LOAD DIAGRAM

MBB R 1500 SK		MBB R 2000 LK	
a (mm)	Q (kg)	a (mm)	Q (kg)
1,000	1,500	750	2,000
1,200	1,250	900	1,650
1,500	1,000	1,100	1,300
1,850	800	1,600	950



FOR MOTOR VEHICLES WITH CLOSE-COUPPLING SYSTEM

WEIGHTS

Aluminium/aluminium
platform type

Platform width (mm) 2,400

Platform height (mm)

1,805 710 kg


WEIGHTS

Steel/aluminium
platform type

Platform width (mm) 2,400

Platform height (mm)

1,600 795 kg



DIMENSIONS

Lifting arm lengths (mm)	700	800	900	1,000	1,100
H (max.) loading height, unloaded	1,200	1,428	1,548	1,651	1,793
H (min.) loading height, loaded	883	1,011	1,006	950	1,023
F (max.) middle of main beam to upper edge of loading floor	650	817	924	977	1,056
K (min.) at dimension F (max.)	618	601	623	721	783
D (min.) installation dimension, minimum	1,630	1,740	1,740	1,840	1,840
F (min.)	508	566	614	569	608
K (max.) at dimension F (min.)	726	820	907	1,040	1,132
G (max.) unloaded (middle of main beam to ground)	550	611	624	674	737
G (min.) loaded	375	445	392	381	415
E (max.) vehicle frame width (max.)	1,070	1,070	1,070	1,070	1,070
E (min.) vehicle frame width (min.)	800	750	800	800	800

TECHNICAL DATA

Type	MBB R 1500 SK	MBB R 2000 LK
Lifting capacity	1,500 kg	2,000 kg
Main beam	180 x 180 mm	180 x 180 mm
Lifting gear hydraulics	2 lifting cylinders / 2 tilting cylinders / 1 moving cylinder	
Lifting arm pitch	700 mm	1100 mm
Load centre, longitudinal	1,000 mm	750 mm
Load centre, across centre	Central, 50% of rated load on one side	
Inclination angle of the platform	0° to -10°	0° to -10°

Some of the tail lifts pictured feature special customer-specific equipment. Country-specific regulations must be considered for the tail lift installation. Dimensions may vary. Subject to technical changes, errors and translation mistakes.

