

# QUADRANT

		3400 RF / RC	3300 RF / RC
<b>Hitching</b>			
PTO shaft speed	rpm	1000	1000
Hydraulic jack		●	●
Ball hitch		○	○
<b>Pick-up</b>			
Width	m	2.35	2.35
DIN raking width	m	2.15	2.15
Number of tine bars		4	4
Ground tracking via two oscillating pick-up castor guide wheels		●	●
<b>Hydraulic connection*</b>		2 single-acting and 1 open return line	2 single-acting and 1 open return line
<b>Crop feed</b>			
Rotor		ROTO FEED / ROTO CUT	ROTO FEED / ROTO CUT
Number of knives		-/25	-/25
Blade group changing		-/0, 12, 13, 25	-/0, 6, 12, 13, 25
Two-phase packer tines		●	●
Switchable pre-chamber (adjustable)		0-4	Automatic, small swath, large swath
<b>Bale chamber</b>			
Ram strokes	rpm	46	46
Max. baling pressure	bar	200	200
Bale ejector		●	●
Bale deposit sensor		○	○
Moisture sensor		○	○
<b>Bale chamber dimensions</b>			
Length	m	3.00	3.00
Width	m	1.20	1.20
Height	m	1.00	0.90
Bale length	m	0.50 to 3.00	0.50 to 3.00
<b>Control terminal</b>			
CLAAS COMMUNICATOR II		●	●
<b>Wrapping and tying</b>			
Number of knotters		6	6
Number of twine reels in the twine box		24 x 11.5 kg	24 x 11.5 kg
TURBO FAN Knotter cleaning		●	●
<b>Axles and tyres</b>			
Single axle		-	710/40 R 22.5 (●)
Tandem axle		500/55 20 (●)	500/55 20 (○)
Steered tandem axle		620/50 R 22.5 (○)	620/50 R 22.5 (○)
		620/55 R 26.5 (○)	
		710/50 R 26.5 (>3.00 m) (○)	
<b>Dimensions and weights</b>			
Width	m	2.97 – 2.99	2.76 – 2.98
Height	m	3.37 – 3.39	3.36 – 3.42
Weight (tandem axle)	kg	12,560 / 12,860	10,860 / 11,260

● Standard ○ Optional – Not available

\* Additional 1 x single-acting for steered tandem axle

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual.

# QUADRANT

		3200 RF / RC / FC	2200 RF / RC ADVANTAGE
<b>Hitching</b>			
PTO shaft speed	rpm	1000	1000
Hydraulic jack		●	●
Ball hitch		○	○
<b>Pick-up</b>			
Width	m	2.35	2.10
DIN raking width	m	2.15	1.90
Number of tine bars		4	4
Ground tracking via two oscillating pick-up castor guide wheels		●	●
<b>Hydraulic connection*</b>		2 single-acting and 1 open return line	1 dual-acting and 1 single-acting
<b>Crop feed</b>			
Rotor		ROTO FEED / ROTO CUT / FINE CUT / SPECIAL CUT	ROTO FEED / ROTO CUT / SPECIAL CUT
Number of knives		- / 25 / 51 / 180	- / 25 / 180
Blade group changing		- / 0, 6, 12, 13, 25 / 0, 12, 13, 26, 51 / -	- / 0, 6, 12, 13, 25 / -
Phase packer tines		2 ●	3 ●
Switchable pre-chamber (adjustable)		Automatic, small swath, large swath	-
<b>Bale chamber</b>			
Ram strokes	rpm	51	51
Max. baling pressure	bar	200	200
Bale ejector with hydraulic ramp		●	○
Bale deposit sensor		○	○ (only with CMT)
Moisture sensor		○	○ (only with CMT)
<b>Bale chamber dimensions</b>			
Length	m	3.00	3.00
Width	m	1.20	1.20
Height	m	0.70	0.70
Bale length	m	0.50 to 3.00	0.50 to 3.00
<b>Control terminal</b>			
CLAAS COMMUNICATOR II		●	-
CLAAS MEDIUM TERMINAL II		-	○ / ●
<b>Wrapping and tying</b>			
Number of knotters		6	6
Number of twine reels in the twine box		24 x 11.5 kg	24 x 11.0 kg
TURBO FAN Knotter cleaning		●	●
<b>Bale drop onto field</b>			
Depositing chute		-	● / -
Mechanically folding roller bale chute		-	○ / ○
Hydraulically folding roller bale chute with ejector		●	○ / ●
<b>Axles and tyres</b>			
Single axle		600/50 22.5 (●)	600/50 22.5 (●)
		710/40 R 22.5 (○)	710/40 R 22.5 (○)
Tandem axle		520/50 17 (○)	520/50 17 (○)
		500/55 20 (○)	500/55 R 20 (○)
Steered tandem axle		500/55 20 (○)	-
		620/50 R 22.5 (○)	-
<b>Dimensions and weights</b>			
Width	m	2.52 – 3.00	2.52 – 2.96
Height	m	2.55 – 2.65	2.56 – 2.60
Weight (single axle)	kg	7970 / 8170 / 8220	6920

● Standard ○ Optional – Not available

QUADRANT 2200 ADVANTAGE options: manual or automatic central lubrication, turbo guard

Specifications