

# S-2500

## HYDROMANN



The showing models can be with extra equipment

### **Snowblowers S-2500**

- > Extra strong frame in 8 mm steel plate
- > Skids and edgshare in Hardox
- > Broader nozzle with galvanize safety grid
- > Revolving support wheels with skidpans.
- > Rear or front hitch
- > Screw with 4 internal blades
- > Kapacity 27 - 40 m<sup>3</sup>/min.

## Technical details: (Snowblower S-2500)

Working width	mm	2500
Width	mm	2500
Lenght	mm	1600
Height without pipe	mm	1015
Height with pipe	mm	2580
Weight	kg	1420
Number of blower wings	stk.	4
Blower diameter	mm	900
Screw diameter	mm	500
Blowing distance	m	15-50
Turning pipe		360°
Requested power	HP	130-180
PTO	rpm./min.	540/-1000
Surface treatment	Primer + 2 Component top coat	



Screw with 4 wings.

- Extra equipment:**
- Hydraulic adjustment for pipe flap
  - Loading pipe
  - Edge wings
  - A-frame
  - SMS/HMV frame
  - Threepoint



Revolving support wheels with skidpans.



Gearbox for 540 / 1000 rpm.

# HYDROMANN

Hydromann a/s  
 Nylandsvej 36  
 DK-6940 Lem St.  
 Tlf.: +45 97 34 12 33  
 Fax: +45 97 34 19 09.  
[www.hydromann.dk](http://www.hydromann.dk)