

S 60|80

- THE SHORTEST WHEELBASE IN ITS CATEGORY
- EXCLUSIVE PATENTED TRANSMISSION
- NARROW STEERING RADIUS
- MAXIMUM STABILITY AND ADHERENCE TO THE GROUND THANKS TO OPTIMAL WEIGHT DISTRIBUTION
- THE MOST ROBUST 50 HP MODEL ON THE MARKET



The complete range for orchards and vineyards

The Goldoni S Series meets all of the needs and requirements of professionals operating in vineyards and orchards: power, manoeuvrability, reliability and performance combine to make these tractors the ideal partner for working in the often challenging conditions that characterise specialised crop applications. One of the key advantages of the S Series is its compact dimensions.

TECHNICAL FEATURES

ENGINE

VM 3 Cyl - 35 kW / 48 HP / 4 Cyl 55 kW 75 HP

3 Cyl Tier IIIA / 4 Cyl Tier IIIB Turbo

Direct injection

TRANSMISSION

Dual Power 16+8, 8+8 transmission with lateral levers

Mechanical Reverse Shuttle

4WD and Mechanical DIFF-lock

HYDRAULIC

Lifting capacity 2300 kg

pump output 38 l/min, open-centre

3 rear mechanical distributors

DRIVER AREA

Semi-platform

DIMENSIONS

Wheelbase: 1690-1831 mm

Weight: 1900 kg

Tyre: 360/70R20

Width (min-max): 1318-1794 mm