

VO-350-355-360 MHI

VO-350-355-360-X MHI

Insulated Articulated Overcenter Aerial Lift

PLATFORM HEIGHT: Up To 60.3' (18.4m)

MAXIMUM REACH, OVERCENTER: 52.2' (15.9m)

MAXIMUM PLATFORM CAPACITY: Up To 800 lbs. (360 kg)

MAXIMUM JIB CAPACITY: 2000lbs. (900Kg)



The **VERSALIFT** product line has grown to encompass models for every market. Whether it be a 29' man lift or a 108' material handler, there is a **VERSALIFT** to get the job done.

For More Information
Versalift
254.399.2100
www.VERSALIFT.com

VO-350-355-360 MHI & X-MHI



Insulated Articulated Overcenter Aerial Lift

SPECIFICATIONS	VO-350 MHI	VO-355 MHI	VO-360 MHI
Height to Bottom of Platform	50.3' (15.3 m)	55.3' (16.9 m)	60.3' (18.4 m)
Working Height	55.3' (16.9 m)	60.3' (18.4 m)	65.3' (19.9 m)
Horizontal Reach Overcenter	42.2' (12.9 m)	47.2' (14.4 m)	52.2' (15.9 m)
Horizontal Reach Non-Overcenter	31.9' (9.7 m)	34.9' (10.6 m)	37.9' (11.6 m)
Max Platform Capacity (Single 1-Man)	450 lbs. (205 kg)	450 lbs. (205 kg)	450 lbs. (205 kg)
Max Platform Capacity (Single 2-Man)	800 lbs. (360 kg)	800 lbs. (360 kg)	600 lbs. (270 kg)
Max Total Platform Capacity (Dual 1-Man)	800 lbs. (360 kg)	800 lbs. (360 kg)	not available
Max Total Platform Capacity Dual 1-Man With Dual Controls	800 lbs. (360 kg)	700 lbs. (320 kg)	not available
Upper Boom Articulation	210°	210°	210°
Lower Boom Articulation	101°	101°	101°
Stowed Travel Height	11' (3.4 m)	11' (3.4 m)	11' (3.4 m)
Maximum Jib Capacity	2000 lbs (900 kg)	2000 lbs (900 kg)	2000 lbs (900 kg)
Lower Boom Lift Eye Capacity	2500 lbs (1100 kg)	2500 lbs (1100 kg)	2500 lbs (1100 kg)
Hydraulic System Pressure	3000 psi (210 kg/cm ²)	3000 psi (210 kg/cm ²)	3000 psi (210 kg/cm ²)
Hydraulic System Type	Open Center	Open Center	Open Center
Upper Boom Insulation Gap	9.5' (2.9 m)	12' (3.7 m)	14.5' (4.4 m)
Lower Boom Insulation Gap	12" (30 cm)	24" (60 cm)	24" (60 cm)
Approximate Weight of Lift with Pedestal	7230 lbs. (3280 kg)	7380 lbs. (3350 kg)	7570 lbs. (3430 kg)

SPECIFICATIONS	VO-350-X MHI	VO-355-X MHI	VO-360-X MHI
Height to Bottom of Platform	50.3' (15.3 m)	55.3' (16.9 m)	60.3' (18.4 m)
Working Height	55.3' (16.9 m)	60.3' (18.4 m)	65.3' (19.9 m)
Horizontal Reach Overcenter	42.2' (12.9 m)	47.2' (14.4 m)	52.2' (15.9 m)
Horizontal Reach Non-Overcenter	39.2' (11.9 m)	43.2' (13.2 m)	47.1' (14.4 m)
Max Platform Capacity (Single 1-Man)	450 lbs. (205 kg)	450 lbs. (205 kg)	450 lbs. (205 kg)
Max Platform Capacity (Single 2-Man)	800 lbs. (360 kg)	800 lbs. (360 kg)	600 lbs. (270 kg)
Max Total Platform Capacity (Dual 1-Man)	800 lbs. (360 kg)	800 lbs. (360 kg)	not available
Max Total Platform Capacity Dual 1-Man With Dual Controls	800 lbs. (360 kg)	700 lbs. (320 kg)	not available
Upper Boom Articulation	210°	210°	210°
Lower Boom Articulation	125°	125°	125°
Stowed Travel Height	11' (3.4 m)	11' (3.4 m)	11' (3.4 m)
Maximum Jib Capacity	2000 lbs (900 kg)	2000 lbs (900 kg)	2000 lbs (900 kg)
Lower Boom Lift Eye Capacity	2500 lbs (1100 kg)	2500 lbs (1100 kg)	2500 lbs (1100 kg)
Hydraulic System Pressure	3000 psi (210 kg/cm ²)	3000 psi (210 kg/cm ²)	3000 psi (210 kg/cm ²)
Hydraulic System Type	Open Center	Open Center	Open Center
Upper Boom Insulation Gap	9.5' (2.9 m)	12' (3.7 m)	14.5' (4.4 m)
Lower Boom Insulation Gap	12" (30 cm)	24" (60 cm)	24" (60 cm)
Approximate Weight of Lift with Pedestal	7560 lbs. (3430 kg)	7710 lbs. (3500 kg)	7910 lbs. (3590 kg)