## VST-7500-I Articulated Telescopic Aerial Device

**108" UPPER BOOM INSULATION GAP** 

24" LOWER BOOM INSERT

PLATFORM CAPACITY: Up to 800 lbs

HORIZONTAL REACH: Up to 46' 10" JIB CAPACITY: Up to 2,000 lbs. WORKING HEIGHT: Up to 80'





The VERSALIFT product line has grown to encompass models for every market. Whether it be a 29' man lift or a 180' material handler, there is a VERSALIFT to get the job done. For more information Versalift 254.399.2100 www.VERSALIFT.com

VERSALIFT – Time Manufacturing 7601 Imperial Drive Waco, Texas 76712 | 254-399-2100 | www.VERSALIFT.com

## VST-7500-I

Articulated Telescopic Aerial Device



## **General Specifications** VST-7500-I (based on 40" frame) 46 ft. 10 in. (14.3 m) Horizontal Reach Maximum Platform Capacity 800 lbs. (360 kg) Maximum Platform Capacity w/ Option Jib Installed 700 lbs. (318 kg) 2000 lbs. (907kg) Maximum Jib Capacity (Optional) 1500 lbs. (680 kg) Lower Boom Lift Eye Capacity (Optional) STANDARD PEDESTAL (based on 40 in. (1.01 m) Frame Height) 75 ft. 0 in. (22.9 m) Height to Bottom of Platform Working Height 80 ft. 0 in. (24.4 m) Stowed Travel Height 12 ft. 5 in. (3.8 m) Weight of Lift w/out Subframes & Outriggers 8500 lbs. (3,850 kg) Weight of Lift w/ Subframe & Dual Radial Outriggers 13000 lbs. (5,897 kg) **HYDRAULIC SYSTEM Operating Pressure** 3,000 psi (210 kg/cm<sup>2</sup>) Flow Rate 10 gpm (38 lpm) Filtration 10 micron return 100 mesh suction System Type **Open Center Power Source** PTO PUMP BOOM ARTICULATION Outer/Inner Boom Articulation -25 to +75° Inner Boom Extension 138 in. (3.5 m) Lower Boom Articulation 0° to +88° Rotation 360° Continuous **INSULATION GAPS** Upper Boom 108 in. (2.7 m) Lower Boom 24 in. (0.6 m) Ambient Temperature Range for Structural Integrity -40 to 125°F (-40 to 52°C) METER NOTE: 1. Specificiations may vary without prior notice 2. Required GVWR can vary significantly with chassis, lift mounting, location, service body, accessories and desired payload. 3. Boom articulation is +/- 2°

## **OPTIONS:**

- •Multiple Outrigger Options
- •Second Set of Tool Power Ports
- •Lifting Eye
- •Outrigger/Boom Interlock System
- •Two-Speed Manual Throttle Control
- •Material Handling Jib & Winch Hydraulic
- Extension and Articulation
  Platform Elevator
  Automatic Boom Latch
  TruGuard
  Back-up Pump

